

POPO 111

DATASHEET | SPECIFICATIONS



CHARACTERISTIC

Design LED lamp designed for representative spaces with the option of being attached or suspended.

USE

- interior
- corridors
- office
- Classrooms
- commercial premises
- representative spaces



TECHNICAL SPECIFICATIONS

ELECTRICAL PARAMETERS	
Light source	» LED
AC voltage	» AC 230 V / 50 Hz
Connection	» terminal block
Driver	» electronic driver
Dimming	» non-dimmable (not labeled) » DALI (DALI)
Emergency module	» NO
LIGHT PARAMETERS	
Optical system	» diffuser
Light distribution	» direct
Color rendering index	» Ra > 80
Color temperature	» 3000 k » 4 000 K
Service life	» > 60 000 hours (L80B10)
CONSTRUCTION	
Housing	» painted aluminum
Color	» white (without markings) » other shades according to the RAL swatch
Surface	» matte
Cover	» opal (DSO)
SAFETY	
Protection class	» I
Ambient operating temperature	» +5 / +35 °C
Luminaire cover	» IP 40
Mounting on normally flammable materials	» YES
MOUNTING	
Type	» fitment (without marking) » suspension (Z)
Recommended height	» max. to 8 m
ACCESSORIES	
Mounting accessories	» according to the variant

This luminaire contains built-in LED lamps.

The lamps cannot be changed in the luminaire.

ELEKTRO-LUMEN | POPO 111 874/2012

VARIANTS

DATASHEET POPO 111

TYPE	POWER	LUMINOUS FLUX	COLOR TEMPERATURE	SERVICE LIFE
Name	Watt (W)	Lumen (lm)	Kelvin (K)	L80B10 (hod.)
POPO 111 875 DSO 25W 840	25	3 600	4 000	> 60 000
POPO 111 875 d1000 DSO 25W 840	25	3 600	4 000	> 60 000
POPO 111 875 d1500 DSO 25W 840	25	3 600	4 000	> 60 000
POPO 111 875 d2000 DSO 25W 840	25	3 600	4 000	> 60 000
POPO 111 1 750 DSO 50W 840	50	7 200	4 000	> 60 000
POPO 111 1 750 d1000 DSO 50W 840	50	7 200	4 000	> 60 000
POPO 111 1 750 d1500 DSO 50W 840	50	7 200	4 000	> 60 000
POPO 111 1 750 d2000 DSO 50W 840	50	7 200	4 000	> 60 000
POPO 111 1 750 d3000 DSO 50W 840	50	7 200	4 000	> 60 000
POPO 111 1 750 d4000 DSO 50W 840	50	7 200	4 000	> 60 000
POPO 111 1 750 d5000 DSO 50W 840	50	7 200	4 000	> 60 000

LEGEND

POPO 111 875 d1000 DSO 25W 840 DALI

- name
- lamp height 111 mm
- lamp diameter
- opal (DSO)
- power (W)
- color rendering index Ra > 80, color temperature 4 000 K
- DALI (DALI)

Optical and electrical parameters tolerance +/- 10%.

DIMENSIONS

POPO 111

