

# ETNA S 111

## DATASHEET | SPECIFICATIONS



### TECHNICAL SPECIFICATIONS

#### ELECTRICAL PARAMETERS

Light source	» LED
AC voltage	» AC 230 V / 50 Hz
Connection	» terminal block
Driver	» electronic driver
Dimming	» non-dimmable (not labeled) » DALI (DALI)
Emergency module	» NO

#### LIGHT PARAMETERS

Optical system	» diffuser
Light distribution	» direct
Color rendering index	» Ra > 80
Color temperature	» 3 000 K » 4 000 K
Service life	» > 60 000 hours (L80B10)

#### CONSTRUCTION

Housing	» painted aluminum
Color	» white (without marking) » other shades according to the RAL swatch
Surface type	» mat
Surface	» opal (DSO)

#### SAFETY

Protection class	» I
Ambient operating temperature	» +5 / +35 °C
Ingress protection	» IP 40
Mounting on normally flammable materials	» YES

#### MOUNTING

Type	» abandonment (S)
Recommended height	» to max. 8 m

#### ACCESSORIES

Mounting accessories	» according to the variant
----------------------	----------------------------

### CHARACTERISTIC

Design LED ceiling light designed for representative spaces.

### USE

- Offices
- Interior
- Classrooms
- Representative spaces
- Corridors
- Commercial premises



This luminaire contains built-in LED lamps.

The lamps cannot be changed in the luminaire.

A++

A+

A

C

D

}

L

E

D

ELEKTRO-LUMEN | ETNA S 111 874/2012

### DIMENSIONS

ETNA S 111



# VARIANTS

## DATASHEET ETNAS 111

TYPE	POWER	LUMINOUS FLUX	COLOR TEMPERATURE	SERVICE LIFE
Name	Watt (W)	Lumen (lm)	Kelvin (K)	L80B10 (hod.)
ETNA S 111 600x600 DSO 35W 840	40	4 800	4 000	> 60 000
ETNA S 111 600x600 DSO 70W 840	80	9 600	4 000	> 60 000
ETNA S 111 900x900 DSO 70W 840	80	9 600	4 000	> 60 000
ETNA S 111 900x900 DSO 140W 840	160	19 200	4 000	> 60 000
ETNA S 111 1 200x1 200 DSO 140W 840	160	19 200	4 000	> 60 000
ETNA S 111 1 200x1 200 DSO 280W 840	320	38 400	4 000	> 60 000

### LEGEND

ETNAS\_111\_900x900\_DSO\_70W\_840\_DALI

	name
	abandonment (S)
	lamp height 111 mm
	lamp dia meter
	opal (DSO)
	powerful variant (W)
	color rendering index Ra > 80, color temperature 4 000 K
	dimming DALI (DALI)

Tolerance optických a elektrických parametrů +/- 10 %.